

PRODUCT DATA SHEET

4T MOTORCYCLE OIL SAE 10W-40

PROLUBE 4T Motorcycle Oil SAE 10W-40 is a proven performance four stroke multigrade motorcycle engine oil, designed for use in high performance air and liquid cooled motorcycle engines operating under a wide variety of conditions, including severe operations.

PROLUBE 4T Motorcycle Oil SAE 10W-40 is formulated with premium quality base oils in combination with shear stable viscosity index (VI) improvers and a robust additive package, providing a multifunctional oil for engines requiring JASO MA2 or MA and SL lubricants, including high specific output engines operating in severe service.

TYPICAL CHARACTERISTIC

Properties		Result
Grade		SAE 10W-40
Density @15°C	kg/l	0.857
Kinematic Viscosity @40°C	cSt	97.5
Kinematic Viscosity @100°C	cSt	14.8
Viscosity Index		160
Viscosity CCS @-25°C	cP	< 7000
Pour Point	°C	-33
Flash Point C.O.C	°C	230
TBN, mg (KOH/g)		7.7
Operating Temperature	°C	-30/150

Health, Safety & Environment

Prolube lubricants unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.