

PRODUCT DATA SHEET

CVT FLUID

UBE CVT FLUID Fully Synthetic is a low viscosity continuously variable transmission fluid formulated to the newest OEM CVT Fluid standard from fully synthetic base oil and a unique additive package. It features anti-foaming properties and excellent vibration-resistance.

APPLICATION

PROLUBE CVT FLUID Fully Synthetic is designed for application in a continuously variable transmissions (CVT), where most Japanese, American, European vehicles is recommended. The product properties are optimized to meet the requirements for continuously variable transmissions.

PROLUBE CVT FLUID provides:

Compliance with the requirements of OEM (Original Equipment Manufacturer)

Exceptional anti-vibration properties.

Correct CVT operation under different operating conditions.

Excellent wear protection.

TYPICAL CHARACTERISTIC

Properties		Result
Density@15°C	kg/m ³	846
Kinematic Viscosity @40°C	cSt	29.79
Kinematic Viscosity @100°C	cSt	7.08
Viscosity Index		160
Pour Point	°C	-45
Flash Point C.O.C	°C	210
Operating Temperature	°C	-40/160

Health, Safety & Environment

Prolube lubricants unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.